

VariablesHelper

Variables

Variables can be used in many different places, e.g. in [Mailtexten](#) (im Detail [here](#)), [actionhandlers](#) or in the [tim.properties](#).

Variable are always marked with `${name_of_the_variable}`.
System variables always have the prefix **SYS**.

System Variables

System variables can be used, when the context allows it. The following variable are therefor always available:

<code>\${SYS.PROCESSDEFINITION_NAME}</code>	Returns the name blonging to the current processdefinition.
<code>\${SYS.PROCESSINSTANCE_NAME}</code>	Returns the name belonging to the current procesinstance.
<code>\${SYS.PROCESSINSTANCE_ID}</code>	Returns the unique ID (number) belonging to the Processinstance. Attention: No connection to YearIdGenerator
<code>\${SYS.PROCESSINSTANCE_DESCRIPTION}</code>	Returns the description belonging to the current Processinstance
<code>\${SYS.PROCESSVARIABLELOG}</code>	Returns a list of the used processvariables.
<code>\${SYS.DOC_HISTORY}</code>	Returns the document history of one processinstance. Contains user, time and date as well as the type of operation (create, edit, delete).
<code>\${SYS.BUSINESS_ID}</code>	This number is increased by 1 for instance, continuesly for every process and client
<code>\${SYS.TASK_NAME}</code>	Returns the current taskname.
<code>\${SYS.NODE_NAME}</code>	Returns the current activityname
<code>\${SYS.TASK_ID}</code>	Returns the unique ID belonging to the current task.
<code>\${SYS.NODE_ID}</code>	Returns the unique ID belonging to the current activity.
<code>\${SYS.TASKLINK}</code>	Returns the link to the current task.
<code>\${SYS.TASK_DESCRIPTION}</code>	Returns the description belonging to the current task.
<code>\${SYS.CLIENT_NAME}</code>	Returns the current clientname.
<code>\${SYS.CLIENT_ID}</code>	Returns the unique ID belonging to the current client.
<code>\${SYS.BASELINK}</code>	Returns the link, which is composed of Client-Profil (Application-Host + Port) and /loom-portal/.
<code>\${SYS.ROOTLINK}</code>	Returns the link, which is composed of Client-Profil (Application-Host + Port).
<code>\${SYS.NOW}</code>	Returns the current server time.
<code>\${SYS.SEZ}</code>	Returns the LFT (Latest Finish Time) of the current task.
<code>\${SYS.RECIPIENT_GROUP_NAME}</code>	Returns the group's name, which should receive this mail.(Notifications at notes)

`\${SYS.RECIPIENT_NAME}`	Returns the user's username, which should receive this mail.(Notifications at notes)
`\${SYS.RECIPIENT_FIRSTNAME}`	Returns the user's first name, which should receive this mail.(Notifications at notes)
`\${SYS.RECIPIENT_LASTNAME}`	Returns the user's last name, which should receive this mail.(Notifications at notes))

From:
<https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link:
<https://wiki.tim-solutions.de/doku.php?id=en:faq:variables-helper&rev=1539075170>

Last update: **2021/07/01 09:56**

