

 **This page is not fully translated, yet. Please help completing the translation.**
(remove this paragraph once the translation is finished)

CallAnafeeWebServiceHandler

Description

Handler to call the ANAFEE Web service.

The results of the sync are written to the variable "ANAFEE4 Synch_result" (from Version 3.5.1 on)

Action Class

```
com.dooris.bpm.actionhandler.CallAnafeeWebServiceHandler
```

Event Type

any

Action Name

any

Mandatory Fields

none

Parameter

Here, there are multiple parameters containing the names of the variable containing the values for Anafee.

Attention! Starting with inventoryNumber, the variable names will be searched for variables ending with the form [number]. The search will continue for higher inventory[5] variables until a prodDesc[5] is no longer present.

For costCenterOrPsp, a search for a variable with [serial number] on the end will be executed. If this is not found, the variable will be used without it.

Examples: lastName=surname;
firstName=firstname;
profitCenterId=profitcenterId;
profitCenterDescription=profitcenterText;
costCenterOrPsp=costcenter;
persId=personalnumber;
inventoryNumber=inventory_id;
chargeGit=charge_git_material_git;
beginningOfTerm=runtimebegin;
endOfTerm=runtimeend;
runtime=runtime;
additionalDescription1=;
additionalDescription2=;
serialId=serial_id;
price=price;
unit=;
invoiceDate=invoicedate;
chargingType=;
deviceState=articleStatus;
anald=;
prodId=articleId;
prodDesc=articleName;

ANAFEE4 Sync_result If the files for Anafee are incomplete or incorrect (for example, if the date invalid or ANAID no number or Anafee not ok is reported), **false** will be written in the "ANAFEE4 Synch_result". Otherwise, it will be **true**.

CallAnafeeErrorMessage

Additionally, the parameter errorMessageVariabelName exists. The standard value is CallAnafeeErrorMessage. In case of an error, a variable with an error message and the name from this variable is generated.

Example

Symboleigenschaften - Contain the problem

Edit Event

Ereignistyp: Node Leave

Aktionsname: CallAnafeeWebServiceHandler

Aktionsklasse: jm.actionhandler.CallAnafeeWebServiceHandler

Mandatory Fields:

Parameter:

```
lastName=nachname;  
firstName=vorname;  
profitCenterId=profitcenterId;  
profitCenterDescription=profitcenterText;  
costCenterOrPsp=kostenstelle;  
persId=personalnummer;  
inventoryNumber=inventar_id;  
chargeGit=charge_git_material_git;  
beginningOfTerm=laufzeitbeginn;  
endOfTerm=laufzeitende;  
runtime=laufzeit; |  
additionalDescription1=;  
additionalDescription2=;  
serialId=serial_id;  
price=preis;  
unit=;  
invoiceDate=rechnungsdatum;  
chargingType=;  
deviceState=artikelStatus;  
analId=;  
prodId=artikelId;  
prodDesc=artikelName;
```

Buttons: OK, Abbrechen

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / **NEW TIM 6 Documentation**

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:callanafeewebsevicehandler>

Last update: **2021/07/01 09:52**

