

 **This page is not fully translated, yet. Please help completing the translation.**  
(remove this paragraph once the translation is finished)

## CallAnafeeWebServiceHandler

Handler to call the ANAFEE Web service.

The results of the sync are written to the variable "ANAFEE4 Synch\_result" (from Version 3.5.1 on)

---

### Action Class

```
com.dooris.bpm.actionhandler.CallAnafeeWebServiceHandler
```

---

### Event Type

any

### Action Name

any

### Mandatory Fields

none

---

### Parameter

Here, there are multiple parameters containing the names of the variable containing the values for Anafee.

**Attention!** Starting with inventoryNumber, the variable names will be searched for variables ending with the form [number]. The search will continue for higher inventory[5] variables until a prodDesc[5] is no longer present.

For costCenterOrPsp, a search for a variable with [serial number] on the end will be executed. If this is not found, the variable will be used without it.

Examples: lastName=surname;  
firstName=firstname;  
profitCenterId=profitcenterId;  
profitCenterDescription=profitcenterText;  
costCenterOrPsp=costcenter;  
persId=personalnumber;  
inventoryNumber=inventory\_id;  
chargeGit=charge\_git\_material\_git;  
beginningOfTerm=runtimebegin;  
endOfTerm=runtimeend;  
runtime=runtime;  
additionalDescription1=;  
additionalDescription2=;  
serialId=serial\_id;  
price=price;  
unit=;  
invoiceDate=invoicedate;  
chargingType=;  
deviceState=articleStatus;  
anald=;  
prodId=articleId;  
prodDesc=articleName;

**ANAFEE4 Sync\_result** If the files for Anafee are incomplete or incorrect (for example, if the date invalid or ANAID no number or Anafee not ok is reported), **false** will be written in the "ANAFEE4 Synchron\_result". Otherwise, it will be **true**.

### **CallAnafeeErrorMessage**

Additionally, the parameter errorMessageVariabelName exists. The standard value is CallAnafeeErrorMessage. In case of an error, a variable with an error message and the name from this variable is generated.

---

## **Example**

Symboleigenschaften - Contain the problem

**Edit Event**

Ereignistyp: Node Leave

Aktionsname: CallAnafeeWebServiceHandler

Aktionsklasse: jm.actionhandler.CallAnafeeWebServiceHandler

Mandatory Fields:

Parameter:

```
lastName=nachname;  
firstName=vorname;  
profitCenterId=profitcenterId;  
profitCenterDescription=profitcenterText;  
costCenterOrPsp=kostenstelle;  
persId=personalnummer;  
inventoryNumber=inventar_id;  
chargeGit=charge_git_material_git;  
beginningOfTerm=laufzeitbeginn;  
endOfTerm=laufzeitende;  
runtime=laufzeit; |  
additionalDescription1=;  
additionalDescription2=;  
serialId=serial_id;  
price=preis;  
unit=;  
invoiceDate=rechnungsdatum;  
chargingType=;  
deviceState=artikelStatus;  
analId=;  
prodId=artikelId;  
prodDesc=artikelName;
```

Buttons: OK, Abbrechen, Übernehmen, Hilfe

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / **NEW TIM 6 Documentation**

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:callanafeewebservicehandler&rev=145553311>

Last update: **2021/07/01 09:54**

