

 **This page is not fully translated, yet. Please help completing the translation.**
(remove this paragraph once the translation is finished)

DayIdGenerator

Description

This action handler creates an ID based on the actual date in ddMMyyyy (or yyyyMMdd) form as well as a serial number. The number is reset and counted anew with each new day.

Action Class

```
com.dooris.bpm.actionhandler.DayIdGenerator
```

Event Type

any type

Action Name

any text

Mandatory Fields

Here, one can define a variable to be written into the generated ID.

Parameter

renameInstance

This parameter is set to "false" by default. If it is set to be "true" (renameInstance=true;), the running instance will be named after the ID (see [example](#))

format

This parameter is set to ddMMyyyy by default. The parameter can also be passed with a yyyyMMdd format (format=yyyyMMdd;), in order to customize the ID (see [example](#))

Example

Symboleigenschaften - Contain the problem

Solldauer: 800

Aufgabenliste:

Aufgabenname	Rollenzuweisung
Contain the problem	

Edit Event

Ereignistyp: Node Leave

Aktionsname: DayIdGenerator

Aktionsklasse: com.dooris.bpm.actionhandler.DayIdGenerator

Mandatory Fields:

Parameter: renameInstance=true;
format=yyyyMMdd;

OK Abbrechen

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / **NEW TIM 6 Documentation**

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:dayidgenerator&rev=1492073424>

Last update: **2021/07/01 09:54**

