

ICalHandler

Description

This [handler](#) allows an appointment, which has been created in a smart form, to be sent to all participants.

Attention! This Handler does not use the Mail queue which means an exception is thrown if no valid mail server is entered in the client profile.

Action Class

```
com.dooris.bpm.actionhandler.ICalHandler
```

Event Type

any

Action Name

any

Mandatory Fields

none

Parameter

eventName

Name of the meeting. May be derived from process variables -> \${processvariable} (see [example](#)).

description

Description of the meeting. May be derived from process variables -> \$(processvariable) (see [example](#)).

location

Location of the meeting. May be derived from process variables -> \$(processvariable) (see [example](#)).

start

Start of the meeting.

i.e. in the format: dd.MM.yyyy HH:mm:ss ⇒ 13.02.2013 17:00:00 (see [Pattern](#))

May be derived from process variables -> \$(processvariable)

(see [example](#)).

end

End of the meeting.

i.e. in the format: dd.MM.yyyy HH:mm:ss ⇒ 13.02.2013 19:00:00 (see [Pattern](#))

May be derived from process variables -> \$(processvariable)

(see [example](#)).

organizer

Organizer of the meeting.

May be derived from process variables -> \$(processvariable)

If the organizer is derived from a process variable:

`#{organizer}`

Process variable: organizerEmail -> Email Address

Process variable: organizerRealName -> Name displayed in the meeting request.

If the organizer is given directly to the handler:

Format: email?name

(Usage of “[selectUsersByGroupByClass](#)” is possible!).
(see [example](#)).

attendant

Participants of the meeting.

May be derived from a process variable -> \$(processvariable)

If the participant is derived from a process variable:

`\${attendant}

attendant[0]Email

attendant[0]RealName

attendant[1]Email

attendant[1]RealName

Or: `\${attendant}` → E-mail addresses are separated by commas!

If the participant is given directly to the handler:

Format: E-mail addresses are separated by commas!

(Usage of “[selectUsersByGroupByClass](#)” is possible!).
(see [example](#)).

datePattern

The pattern depicting how the date variables are formatted.

z.B.: dd.MM.yyyy


fullTime

Controls if the last day of the entry should be counted as an all-day event. This is set to false by default.

Example: fullTime = true;

Example

Possible smartform:

Eigenschaften *Smartform 

Name:

Ort:

Beschreibung:

Start:

Ende:

Organisator:

Teilnehmer:

Parameter possibility 1:

```
Parameter eventName=${name};
location=${ort};
description=${beschreibung};
start=${start};
end=${ende};
attendant=${attend};
organizer=${organisator};
datePattem=dd.MM.yyyy;
```

Parameter possibility 2:

```

Parameter
eventName=${name};
location=${ort};
description=${beschreibung};
start=${start};
end=${ende};
attendant=stefan.barth@tim-solutions.de?Stefan Barth;
organizer=fabian.tagsold@tim-solutions.de?Fabian Tagsold;
datePattern=dd.MM.yyyy;

```

E-mail:

Meeting Request: Doku Test Posteingang

fabian.tagsold@tim-solutions.de
an mich

13:09 (vor 7 Minuten)

<p>Titel: Doku Test</p> <p>Zeitpunkt: So 24. Feb. 15:30 – Mo 25. Feb. 2013 16:00 (MEZ)</p> <p>Wo: Wiki</p> <p>Wer: fabian.tagsold@tim-solutions.de*</p> <p>Detaillierte Informationen »</p> <p>Teilnehmen? Ja - Vielleicht - Nein</p>	<p>Übersicht für So 24. Feb. 2013</p> <p>Keine früheren Veranstaltungen</p> <p>15:30 Doku Test</p> <p>Keine späteren Termine</p> <p>Kalender ansehen »</p>
---	--

invite.ics
1 K Herunterladen

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:icalhandler&rev=1503493835>

Last update: **2021/07/01 09:54**

