

IdGenerationActionhandler

This handler generates a ID and saves this in a process variable. The difference to [yearidgenerator](#) is that no current yearnumber is set before the ID.

class

```
com.dooris.bpm.actionhandler.IDGenerationActionHandler
```

Event Type

any

Action Name

any

Mandatory Fields

empty

Parameter

processVariable

Here the name of the process variable can be given, in which the ID should be saved.

length

With **length** the length of the ID can be determined. If this parameter is not used, the langth is 4 characters long.

resetBy

With this parameter it can be determined, how often the ID should be reset. If this parameter is not used, the ID will be reset to 0000 for every calendar year and starts new. Available options are:

- year
 - month
-

example

Automation Properties >

< Back to Automation

Name
IdGen

Event Type
Node Enter

Event Class
com.dooris.bpm.actionhandler.IDGenerationAction


Mandatory Fields

Add new parameter

Name
processVariable

Value
id_der_variable

SAVE PARAMETER Cancel



Automation Properties >

< Back to Automation

Name
IdGen

Event Type
Node Enter ▾

Event Class
com.dooris.bpm.actionhandler.IDGenerationAction

Mandatory Fields

Add new parameter

Name	length
Value	6

SAVE PARAMETER Cancel

From:
<https://wiki.tim-solutions.de/> - TIM Wiki / [NEW TIM 6 Documentation](#)

Permanent link:
<https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:idgenerationactionhandler&rev=1515662411>

Last update: **2021/07/01 09:54**

