

RenameInstanceHandler

Description

This [handler](#) renames the current instance by any text that can include variables.

==== Action Class ====

```
com.dooris.bpm.actionhandler.RenameInstanceHandler
```

Event Type

any type

Action Name

any name

Mandatory Fields

-

Parameter

instanceName = desired_name_\${variable}

Variables are specified as \${variablename} (see [Example](#))

A continuous ID for process instances

The process variable \${processInstanceId} generates a unique ID for every created process instance. The variable can be used in the renameInstanceHandler. Thus, every created process instance is given a unique ID.

Example

Symboleigenschaften - Archivieren

The screenshot shows a software interface for editing BPMN elements. A sidebar on the left lists various categories, with 'Automatisierung' highlighted. The main workspace displays an 'Ereignisliste' (Event List) with a context menu open, showing the 'Edit Event' dialog. The dialog fields are as follows:

- Ereignistyp: Node Enter
- Aktionsname: RenameInstanceHandler
- Aktionsklasse: com.dooris.bpm.actionhandler.RenameInstanceHandler
- Mandatory Fields: (empty)
- Parameter: instanceName=Testinstance_\$(date);

Buttons for 'OK', 'Abbrechen', and 'Übernehmen' are visible at the bottom of the dialog and the main workspace.

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / **NEW TIM 6 Documentation**

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:renameinstancehandler>

Last update: **2021/07/01 09:52**

