

# RenameInstanceHandler

## Description

This [handler](#) renames the current instance by any text that can include variables.

---

## Action Class

```
com.dooris.bpm.actionhandler.RenameInstanceHandler
```

---

## Event Type

any type

## Action Name

any name

## Mandatory Fields

-

## Parameter

**instanceName = desired\_name\_\${variable}**

Variables are specified as `${variablename}` (see [Example](#))

### A continuous ID for process instances

The [system variable](#) `${SYS.BUSINESS_ID}` generates a unique, continuous ID for every created process instance. The system variable can be used in the `renameInstanceHandler`. Thus, every created process instance is given a unique, continuous ID.

### Automation Properties

[← Back to Automation](#)

Name

Rename Instance

Event Type

Node Enter ▼

Event Class

com.dooris.bpm.actionhandler.RenameInstanceHa

Mandatory Fields

#### Add new parameter

Name

instanceName

Value

\${SYS.BUSINESS\_ID}

**SAVE PARAMETER**

Cancel

---

## Example

Symboleigenschaften - Archivieren

Ereignisliste:

**Edit Event**

Ereignistyp: Node Enter

Aktionsname: RenameInstanceHandler

Aktionsklasse: com.dooris.bpm.actionhandler.RenameInstanceHandler

Mandatory Fields:

Parameter: instanceName=Testinstance\_\$(date);

OK Abbrechen

OK Abbrechen Übernehmen Hilfe

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / **NEW TIM 6 Documentation**

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:renameinstancehandler&rev=1492073489>

Last update: **2021/07/01 09:54**

