

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.  
(remove this paragraph once the translation is finished)

# SetMilestonesFromDateFromTaskDescription

## Description

The handler must be set to the first activity with event type **Node-Enter**.  
Two parameters are given to the handler: the **searchPattern** and the **datePattern**.  
Upon execution, all of the task descriptions on the searchPattern will be assessed, and if something is found, the datePattern will be employed to generate a date from the found material.  
The generated date is added to the superordinate activity as a milestone.  
If an activity has multiple tasks, the first date found will be used. Therefore, each task description in an activity should have the same date.  
The date found in the task description must be surrounded by square brackets!

---

## Action Class

```
com.dooris.bpm.actionhandler.SetMilestonesFromDateFromTaskDescription
```

---

## Event Type

Node Enter

## Action Name

any name

## Mandatory Fields

none

---

## Parameter

## searchPattern

The regex with which the task description is searched.

Beispiel:

```
\d\d\. \d\d\. \d\d\d\d
```

## datePattern

The pattern by which the date for the string (found via the regex) is generated.

It must match the searchPattern!

Based on the aforementioned "searchPattern":

```
dd.MM.yyyy (works)  
dd.MM.yy (does NOT work!)
```

**CAUTION: THE DATE IN THE TASK DESCRIPTION MUST BE SURROUNDED BY SQUARE BRACKETS!!**

**THE REGEX WILL AUTOMATICALLY BE ADDED TO THIS!!**

---

## Example

[Task description:](#)

Symboleigenschaften - Archivieren

Symbol

BPMN-Anleitung

Modellierung

Eingaben

Ressourcen

Aufgabe

Ausgaben

Attribute

Letzte Simulation

Sonstige

Allgemein

Verknüpfungen

Benutzerdefinierte Daten

Risiken

Messgrößen

RACI

**Automatisierung**

Enterprise

Beschreibt

Solldauer:

Aufgabenliste:

Aufgabenname	Rollenzuweisung
Taskbeschreibung mit korrektem Datum [14. 12. 2015]	

Ereignisliste:

Ereignistyp	Aktionsname	Aktionsklasse	Mandatory Fields	Parameter
Node Enter	SetMilestonesFromDate	com.dooris.bpm.actionh		searchPattern=\\d\\d\\.\\d\\d datePattern=dd.MM.yy

OK Abbrechen Übernehmen Hilfe

Handler configuration:

### Symboleigenschaften - Archivieren

The screenshot shows a software interface for editing BPMN symbols. A dialog box titled "Edit Event" is open, displaying the following configuration:

- Ereignistyp:** Node Enter
- Aktionsname:** SetMilestonesFromDateFromTaskDescription
- Aktionsklasse:** com.dooris.bpm.actionhandler.SetMilestonesFromDateFromTaskDescription
- Mandatory Fields:** (empty)
- Parameter:** searchPattern=\d\d\\.\\d\d\\.\\d\d\d\d; datePattern=dd.MM.yyyy;

The background interface shows a table with columns: Ereignistyp, Aktionsname, Aktionsklasse, Mandatory Fields, and Parameter. The "Übernehmen" button is highlighted in the bottom right of the dialog.

From: <https://wiki.tim-solutions.de/> - [TIM Wiki](#) / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:setmilestonesfromdatefromtaskdescription>

Last update: **2021/07/01 09:52**

