

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.
(remove this paragraph once the translation is finished)

SetMilestonesFromDateFromTaskDescription

Description

The handler must be set to the first activity with event type **Node-Enter**.
Two parameters are given to the handler: the **searchPattern** and the **datePattern**.
Upon execution, all of the task descriptions on the searchPattern will be assessed, and if something is found, the datePattern will be employed to generate a date from the found material.
The generated date is added to the superordinate activity as a milestone.
If an activity has multiple tasks, the first date found will be used. Therefore, each task description in an activity should have the same date.
The date found in the task description must be surrounded by square brackets!

Action Class

```
com.dooris.bpm.actionhandler.SetMilestonesFromDateFromTaskDescription
```

Event Type

Node Enter

Action Name

any name

Mandatory Fields

none

Parameter

searchPattern

The regex with which the task description is searched.

Beispiel:

```
\d\d\d\.\d\d\d\.\d\d\d\d\d
```

datePattern

The pattern by which the date for the string (found via the regex) is generated.

It must match the searchPattern!

Based on the aforementioned "searchPattern":

```
dd.MM.yyyy (works)  
dd.MM.yy (does NOT work!)
```

CAUTION: THE DATE IN THE TASK DESCRIPTION MUST BE SURROUNDED BY SQUARE BRACKETS!!
THE REGEX WILL AUTOMATICALLY BE ADDED TO THIS!!

Example

[Task description:](#)

Symboleigenschaften - Archivieren

Symbol
BPMN-Anleitung
Modellierung
Eingaben
Ressourcen
Aufgabe
Ausgaben
Attribute
Letzte Simulation
Sonstige
Allgemein
Verknüpfungen
Benutzerdefinierte Daten
Risiken
Messgrößen
RACI
Automatisierung
Enterprise
Beschreibt

Solldauer:

Aufgabenliste:

Aufgabenname	Rollenzuweisung
Taskbeschreibung mit korrektem Datum [14. 12. 2015]	

Ereignisliste:

Ereignistyp	Aktionsname	Aktionsklasse	Mandatory Fields	Parameter
Node Enter	SetMilestonesFromDate	com.dooris.bpm.actionh		searchPattern=\\d\\d\\.\\d\\d datePattern=dd.MM.yy

OK Abbrechen Übernehmen Hilfe

Handler configuration:

Symboleigenschaften - Archivieren

The screenshot shows a software interface for editing BPMN symbols. A dialog box titled "Edit Event" is open, allowing configuration of an event. The event type is set to "Node Enter". The action name is "SetMilestonesFromDateFromTaskDescription" and the action class is "com.dooris.bpm.actionhandler.SetMilestonesFromDateFromTaskDescription". The parameters field contains the following text: `searchPattern=\\d\\d\\.\\d\\d\\.\\d\\d\\d\\d;` and `datePattern=dd.MM.yyyy;`. The background interface includes a table with columns for "Ereignistyp", "Aktionsname", "Aktionsklasse", "Mandatory Fields", and "Parameter".

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:setmilestonesfromdatefromtaskdescription&rev=1492073583>

Last update: **2021/07/01 09:54**

