

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.
(remove this paragraph once the translation is finished)

SetStarterByProcessVariableHandler

Description

This uses a process variable to designate an arbitrary user as an instance-starter.

Action Class

```
com.dooris.bpm.actionhandler.SetStarterByProcessVariableHandler
```

Event Type

node-enter

Action Name

any

Mandatory Fields

-

Parameter

processVariable = Name_of_Variable;

Up to Version 4.2, only the username is valid as variable content (i.e. "stefan.meier"). From Version 4.2 on, the variable can contain the username and the e-mail address (i.e. "stefan.meier@tim.de").

Example

Symboleigenschaften - Archivieren

Symbol: Solldauer:

BPMN-Anleitung

Modellierung: Aufgabenliste: + ↑ ↓ ↻ ✖

Eingaben

Ressourcen

Aufgabe

Ausgaben

Attribute

Letzte Simulation

Sonstige

Allgemein

Verknüpfungen

Benutzerdefinierte

Risiken

Messgrößen

RACI

Automatisierung

Enterprise

Beschreibt

Edit Event ✕

Ereignistyp:

Aktionsname:

Aktionsklasse:

Mandatory Fields:

Parameter:

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:setstarterbyprocessvariablehandler>

Last update: **2021/07/01 09:52**

