

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.
(remove this paragraph once the translation is finished)

SetStarterByProcessVariableHandler

This uses a process variable to designate an arbitrary user as an instance-starter.

Action Class

```
com.dooris.bpm.actionhandler.SetStarterByProcessVariableHandler
```

Event Type

node-enter

Action Name

any

Mandatory Fields

-

Parameter

processVariable = Name_of_Variable;

Up to Version 4.2, only the username is valid as variable content (i.e. "stefan.meier"). From Version 4.2 on, the variable can contain the username and the e-mail address (i.e. "stefan.meier@tim.de").

Example

Symboleigenschaften - Archivieren

The screenshot displays a software interface for editing event properties. A central dialog box titled "Edit Event" is open, showing the following configuration:

- Ereignistyp:** Node Enter
- Aktionsname:** SetStarterByProcessVariableHandler
- Aktionsklasse:** com.dooris.bpm.actionhandler.SetStarterByProcessVariableHandler
- Mandatory Fields:** (empty)
- Parameter:** processVariable=Name_derVariable;

The background interface includes a sidebar with a tree view containing categories such as "Eingaben", "Ressourcen", "Aufgabe", "Ausgaben", "Attribute", "Letzte Simulation", "Sonstige", "Allgemein", "Verknüpfungen", "Benutzerdefinierte", "Risiken", "Messgrößen", "RACI", "Automatisierung", "Enterprise", and "Beschreibt". The "Automatisierung" category is currently selected. At the bottom of the main window, there are buttons for "OK", "Abbrechen", "Übernehmen", and "Hilfe".

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:setstarterbyprocessvariablehandler&rev=1453218594>

Last update: **2021/07/01 09:54**

