

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.
(remove this paragraph once the translation is finished)

SetStarterByProcessVariableHandler

Description

This uses a process variable to designate an arbitrary user as an instance-starter.

Action Class

```
com.dooris.bpm.actionhandler.SetStarterByProcessVariableHandler
```

Event Type

node-enter

Action Name

any

Mandatory Fields

-

Parameter

processVariable = Name_of_Variable;

Up to Version 4.2, only the username is valid as variable content (i.e. "stefan.meier"). From Version 4.2 on, the variable can contain the username and the e-mail address (i.e. "stefan.meier@tim.de").

Example

Symboleigenschaften - Archivieren

The screenshot displays a software interface for editing event properties. A dialog box titled "Edit Event" is open, showing the following configuration:

- Ereignistyp:** Node Enter
- Aktionsname:** SetStarterByProcessVariableHandler
- Aktionsklasse:** com.dooris.bpm.actionhandler.SetStarterByProcessVariableHandler
- Mandatory Fields:** (empty)
- Parameter:** processVariable=Name_derVariable;

The background interface includes a sidebar with categories such as "Eingaben", "Ressourcen", "Aufgabe", "Ausgaben", "Attribute", "Letzte Simulation", "Sonstige", "Allgemein", "Verknüpfungen", "Benutzerdefinierte", "Risiken", "Messgrößen", "RACI", "Automatisierung", "Enterprise", and "Beschreibt". The main area shows a task list with a table containing columns for "Symbol", "Solldauer", and "Aufgabenliste".

From: <https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:actionhandler:setstarterbyprocessvariablehandler&rev=1492073851>

Last update: **2021/07/01 09:54**

