

 **This page is not fully translated, yet. Please help completing the translation.**
(remove this paragraph once the translation is finished)

setProcessVariableAndSignalProcessInstanceByTransitionName

This timer writes process variable and forwards instance based on activity name and transition name.

IMPORTANT! Is mostly used in combination with the [decision by email](#). In this case, the Webservice as SOAP-call is to execute. As a completely configured timer in the admin client makes this less sense.

Webservice Name

ProcessInstanceManager

Webservice Methode

setProcessVariableAndSignalProcessInstanceByTransitionName

Parameter

Parameter1

ProcessInstanceld

Link call up: args[0](see [Example](#))

Parameter 2

Variables name

Link call up: args[1] (see [Example](#))

Parameter 3

Variables value

Link call up: args[2] (see [Example](#))

Parameter 4

Activity name

Link call up: args[3] (see [\[#Example\]](#))

Parameter 5

Transition name

Link call up: args[4] (see [\[#Example\]](#))

Only for link call up

uid: Encoding login data for TIM Base64 (client/user:password)

Example

```
http://URL des Servers/loom-portal/ProcessInstanceManager/setProcessVariableAndSignalProcessInstanceByTransitionName.soap?args[0]={processInstanceId}&args[1]=VARIABLESNAME&args[2]=VARIABLESVALUE&args[3]=ACTIVITYNAME&args[4]=TRANSITIONNAME&i=1&uid=LOGINDATA
```

Dependencies

T!M Version :

From: <https://wiki.tim-solutions.de/> - TIM Wiki / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=en:software:tim:timer:setprocessvariableandsignalprocessinstancebytransitionname&rev=1418743919>

Last update: 2021/07/01 09:55

