

signalByMail

Description

This [timer](#) checks a mailbox for new mails and forwards the corresponding process instance.

Timer Name

any name

Webservice Name

ProcessInstanceManager

Webservice Method

signalByMailWithLimitAndMoveMessage

Parameter

ProcessInstanceId-Reg-Exp

pildRegex, a [regular expression](#), that specifies how the ProcessInstanceId is found. It searches in the text and in the subject for this.

Aktivitynames-Reg-Exp

nodeNameRegex, a [regular expression](#) that searches the currently processed mail of the given activity and signals it. It searches in texts and in subjects on the server for this.

Filter-Reg-Exp

filterRegex, a [regular expression](#) that specifies the conditions under which mails are to be processed.

IMPORTANT!

If parts of the [regular expression](#) are set in (), they will still be searched but will not be a part of the return value.(e.g.the PI-ID)

Example:

```
(args\[3\] =) [A-Za-z_0-9]* (\&args\[4\] =)
```

returns a text with uppercase and lowercase letters, underscore and numbers when it is located between args[3]= and &args[4]

E-Mail-address

the complete e-mail address from which the mails are retrieved.

Password

the password of the E-Mail account

Port

the port corresponding to the e-mail address and the host

Host

host, e.g. pop3.gmail.com

Example

```
"(\?args\[0\] =) [0-9]{4} (\&args\[1\] =)", "(args\[3\] =) [A-Za-z_0-9]* (\&args\[4\] =)", "", johnm1477@gmail.com, &elam!sILI, 995, pop.gmail.com
```

Dependencies

TIM Version : [Version 3.5.1](#)

From:

<https://wiki.tim-solutions.de/> - TIM Wiki / **NEW TIM 6 Documentation**



Permanent link:

<https://wiki.tim-solutions.de/doku.php?id=en:software:tim:timer:signalbymail&rev=1455879482>

Last update: **2021/07/01 09:55**