

T!M Datenbank Views

Um mit dem Dashboard arbeiten zu können, müssen zuerst die entsprechenden Views angelegt werden, die die T!M Daten aufbereiten und einen einfacheren und schlankeren Zugriff gewähren. Die einzelnen Abschnitte können entweder einfach in den entsprechenden MySQL Client kopiert und ausgeführt werden (Strg + Enter). Alternativ, kann das Script herunter geladen werden und auf dem MySQL Server ausgeführt werden.

[tim_views.sql](#)

```
CREATE DEFINER=`root`@`localhost` FUNCTION `currentClient`() RETURNS  
INT(11)  
NO SQL  
DETERMINISTIC  
RETURN @currentClient;
```

```
CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY  
DEFINER VIEW `view_activity` AS SELECT  
`ni`.`ID_` AS `id`,  
`ni`.`NAME_` AS `name`,  
`ni`.`client_ID_` AS `clientId`,  
`ni`.`CREATION_TIME_` AS `creationTime`,  
`ni`.`creationUser_ID_` AS `creationUserId`,  
`ni`.`processInstance_ID_` AS `instanceId`,  
`ni`.`realStart` AS `start`,  
`ni`.`realEnd` AS `end`,  
`ni`.`loopCount` AS `loopCount`,  
`ni`.`duration` AS `duration`,  
`ni`.`escalationTime` AS `escalationTime`,  
`ni`.`estimatedEnd` AS `estimatedEnd`,  
`ni`.`desiredStart` AS `milestone`,  
`ni`.`desiredStartTime` AS `milestoneDate`,  
`ni`.`inTime` AS `inTime`,  
`ni`.`puffer` AS `timeBuffer`,  
`ni`.`calFAZ` AS `calculatedEST`,  
`ni`.`calFEZ` AS `calculatedEFT`,  
`ni`.`calSAZ` AS `calculatedLST`,  
`ni`.`calSEZ` AS `calculatedLFT`,  
`ni`.`numFAZ` AS `valueEST`,  
`ni`.`numFEZ` AS `valueEFT`,  
`ni`.`numSAZ` AS `valueLST`,  
`ni`.`numSEZ` AS `valueLFT`,  
`node`.`CLASS_` AS `type`  
FROM ((`LOOM_NODEINSTANCE` `ni` JOIN `LOOM_NODE` `node` ON  
(`ni`.`node_ID_` = `node`.`ID_`))) WHERE (`ni`.`client_ID_` =  
`currentClient`());
```

```
CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_definition` AS SELECT
`LOOM_PROCESSDEFINITION`.`ID_` AS `id`,
`LOOM_PROCESSDEFINITION`.`NAME_` AS `name`,
`LOOM_PROCESSDEFINITION`.`CLIENT_` AS `clientId`,
`LOOM_PROCESSDEFINITION`.`CREATION_TIME_` AS `creationTime`,
`LOOM_PROCESSDEFINITION`.`CREATION_USER_` AS `creationUserId`,
`LOOM_PROCESSDEFINITION`.`DESCRIPTION_` AS `description`,
`LOOM_PROCESSDEFINITION`.`VERSION_` AS `version`,
`LOOM_PROCESSDEFINITION`.`ESCALATIONSTATUS_` AS `escalationStatus`,
`LOOM_PROCESSDEFINITION`.`OWNER_EXPRESSION_` AS `owner`,
`LOOM_PROCESSDEFINITION`.`STARTER_EXPRESSION_` AS `starter`,
`LOOM_PROCESSDEFINITION`.`DEPLOYER_EXPRESSION_` AS `deployer`,
`LOOM_PROCESSDEFINITION`.`ARCHIV_` AS `archived`
FROM `LOOM_PROCESSDEFINITION` WHERE (`LOOM_PROCESSDEFINITION`.`CLIENT_`
= `currentClient`());
```

```
CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_effort` AS SELECT
`eff`.`ID_` AS `id`,
`eff`.`NAME_` AS `name`,
`eff`.`client_ID_` AS `clientId`,
`eff`.`CREATION_TIME_` AS `creationTime`,
`eff`.`creationUser_ID_` AS `creationUserId`,
`eff`.`CLASS_` AS `effortType`,
`eff`.`effort` AS `value`,
`eff`.`description` AS `description`,
`eff`.`costCenter_ID_` AS `costCenterId`,
`ti`.`PROCINST_` AS `instanceId`,
`eff`.`parentFolder_ID_` AS `parentFolderId`
FROM (`LOOM_EFFORT` `eff` JOIN `LOOM_TASKINSTANCE` `ti`
ON((`eff`.`parentFolder_ID_` = `ti`.`PARENT_FOLDER_`)))
WHERE (`eff`.`client_ID_` = `currentClient`());
```

```
CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_identity` AS SELECT
`LOOM_IDENTITY`.`ID_` AS `id`,
`LOOM_IDENTITY`.`NAME_` AS `name`,
concat(`LOOM_IDENTITY`.`namelast`,` `,`LOOM_IDENTITY`.`namefirst`,`
`,`LOOM_IDENTITY`.`NAME_`,``) AS `displayName`,
`LOOM_IDENTITY`.`client_ID_` AS `clientId`,
```

```

`LOOM_IDENTITY`.`CREATION_TIME` AS `creationTime`,
`LOOM_IDENTITY`.`creationUser_ID` AS `creationUserId`,
`LOOM_IDENTITY`.`CLASS` AS `identityType`,
`LOOM_IDENTITY`.`email` AS `email`,
`LOOM_IDENTITY`.`namefirst` AS `firstname`,
`LOOM_IDENTITY`.`namelast` AS `lastname`,
`LOOM_IDENTITY`.`ARCHIV` AS `archived`,
`LOOM_IDENTITY`.`blocked` AS `blocked`,
`LOOM_IDENTITY`.`parent_ID` AS `parentID`
FROM `LOOM_IDENTITY` WHERE (`LOOM_IDENTITY`.`client_ID` =
`currentClient`());

```

```

CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_instance` AS SELECT
`pi`.`ID` AS `id`,
`pi`.`NAME` AS `name`,
`pd`.`NAME` AS `definitionName`,
`pi`.`CLIENT` AS `clientId`,
`pi`.`CREATION_TIME` AS `creationTime`,
`pi`.`key` AS `key`,
`pi`.`CREATION_USER` AS `creationUserId`,
`pi`.`PROCESSDEFINITION` AS `definitionId`,
`pi`.`DESCRIPTION` AS `instanceDescription`,
`pi`.`CREATION_GROUP` AS `creationGroup`,
`pi`.`END` AS `end`,
`pi`.`ARCHIV` AS `archiv`,
`pi`.`ARCHIVATIONUSER_ID` AS `archivationUserId`,
`pi`.`ROOTTOKEN` AS `rootToken`,
`pi`.`SUPERPROCESSTOKEN` AS `parentProcessToken`,
`pi`.`NEXT_ESCALATIONTIME` AS `nextEscalationTime`,
`pi`.`processVariableIndex_ID` AS `processVariableIndexId`,
`pi`.`inTime` AS `inTime`,
`pvi`.`field1` AS `index1`,
`pvi`.`value1` AS `value1`,
`pvi`.`field2` AS `index2`,
`pvi`.`value2` AS `value2`,
`pvi`.`field3` AS `index3`,
`pvi`.`value3` AS `value3`,
`pvi`.`field4` AS `index4`,
`pvi`.`value4` AS `value4`,
`pvi`.`field5` AS `index5`,
`pvi`.`value5` AS `value5`,
`pvi`.`field6` AS `index6`,
`pvi`.`value6` AS `value6`,
`pvi`.`field7` AS `index7`,
`pvi`.`value7` AS `value7`,
`pvi`.`field8` AS `index8`,
`pvi`.`value8` AS `value8`,

```

```
`pvi`.`field9` AS `index9`,
`pvi`.`value9` AS `value9`,
`pvi`.`field10` AS `index10`,
`pvi`.`value10` AS `value10`
FROM (((`LOOM_PROCESSINSTANCE` `pi` JOIN `LOOM_PROCESSVARIABLEINDEX`
`pvi` ON (`pi`.`processVariableIndex_ID` = `pvi`.`ID`))) JOIN
`LOOM_PROCESSDEFINITION` `pd` ON((`pi`.`PROCESSDEFINITION` =
`pd`.`ID`)))
WHERE (`pi`.`CLIENT` = `currentClient`());

CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_swimlane` AS SELECT
`LOOM_SWIMLANEINSTANCE`.`ID` AS `id`,
`LOOM_SWIMLANEINSTANCE`.`NAME` AS `name`,
`LOOM_SWIMLANEINSTANCE`.`CLIENT` AS `clientId`,
`LOOM_SWIMLANEINSTANCE`.`PROCINST` AS `instanceId`,
`LOOM_SWIMLANEINSTANCE`.`ACTOR` AS `actor`,
`LOOM_SWIMLANEINSTANCE`.`POOLEDACTOR` AS `pooledActor`
FROM `LOOM_SWIMLANEINSTANCE` WHERE (`LOOM_SWIMLANEINSTANCE`.`CLIENT` =
`currentClient`());

CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_task` AS SELECT
`ti`.`ID` AS `id`,
`ti`.`NAME` AS `name`,
`ti`.`CLIENT` AS `clientId`,
`ti`.`CREATION_TIME` AS `creationTime`,
`ti`.`CREATION_USER` AS `creationUserId`,
`ti`.`PROCINST` AS `instanceId`,
`ti`.`DESCRIPTION` AS `description`,
`ti`.`START` AS `start`,
`ti`.`END` AS `end`,
`ti`.`ISOPEN` AS `isOpen`,
`ti`.`SWIMLANEINSTANCE` AS `swimlaneId`,
`ti`.`ACTOR` AS `actor`,
`ti`.`POOLEDACTOR` AS `pooledActor`,
`ti`.`NODEINSTANCE` AS `activity`,
`ta`.`ISADHOC` AS `isAdhoc`,
`ti`.`PARENT_FOLDER` AS `parentFolderId`,
`ti`.`archiv` AS `archiv`
FROM (`LOOM_TASKINSTANCE` `ti` JOIN `LOOM_TASK` `ta` ON((`ti`.`TASK` =
`ta`.`ID`))) WHERE (`ti`.`CLIENT` = `currentClient`());
```

```
CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_token` AS SELECT
`tok`.`ID_` AS `id`,
`tok`.`NAME_` AS `name`,
`pi`.`CLIENT_` AS `clientId`,
`tok`.`NODEINSTANCE_` AS `nodeInstance`,
`tok`.`PROCESSINSTANCE_` AS `instanceId`,
`tok`.`PARENT_` AS `parent`
FROM (`LOOM_TOKEN` `tok` JOIN `LOOM_PROCESSINSTANCE` `pi`
ON((`tok`.`PROCESSINSTANCE_` = `pi`.`ID_`))) WHERE (`pi`.`CLIENT_` =
`currentClient`());
```

```
CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_variable` AS SELECT
`vi`.`ID_` AS `id`,
`vi`.`NAME_` AS `name`,
`pi`.`CLIENT_` AS `clientId`,
`vi`.`PROCESSINSTANCE_` AS `instanceId`,
`vi`.`StringValue_` AS `stringValue`,
`vi`.`label_` AS `label`
FROM (`LOOM_VARIABLEINSTANCE` `vi` JOIN `LOOM_PROCESSINSTANCE` `pi`
ON((`vi`.`PROCESSINSTANCE_` = `pi`.`ID_`))) WHERE (`pi`.`CLIENT_` =
`currentClient`());
```

```
CREATE ALGORITHM=UNDEFINED DEFINER=`root`@`localhost` SQL SECURITY
DEFINER VIEW `view_role` AS SELECT
`LOOM_IDENTITY_ID_` AS `identityId`,
`ROLE_ID_` AS `roleId`
FROM `MN_IDENTITY_ROLE`;
```

Sobald die Views angelegt sind, können diese mit Hilfe der beschriebenen [TIM Tabellenstruktur](#) für Auswertungen mit dem [TIM Dashboard](#) verwendet werden.

From:
<https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link:
https://wiki.tim-solutions.de/doku.php?id=software:dashboard:dashboard_views&rev=1418743919

Last update: **2021/07/01 10:00**

