

# createProcessInstanceByCSVHandler

## Description

This handler reads all of the files in a folder, starts a process instance for every CSV-file, and names it after the file. The file is then attached to the process.

---

## Timer Name

any

## Web service Name

ProcessInstanceManager

## Web service Method

createProcessInstancesByHandler

---

## Parameter

### Process definition

Name of the process definition to-be started.

### File path

Path to the folder from which the file is to be read.

### Name of the process instance

The name is taken from the columns of the CSV file. For example, if 1~2 is given with the parameter, the resulting name will be Spalte1Spalte2.

## Limit

Here, a maximum for the number of runs that a timer undergoes may be set for the instance.

**Caution!** The file will not be moved.

## Example



Timer Name:

TimerForCreateProcessInstancebyCSVHandler

Webservice Name:

ProcessInstanceManager

Webservice Method:

createProcessInstancesByHandler

Parameter:

Handler,Parameter1;Parameter2;Parameter3

com.dooris.bpm.beans.impl.CreateProcessInstancebyCSVHandler,/usr/local/tim/jboss/server/default/deploy/loom.ear/loom-portal.war/custom/markus/Markus.csv;InstanceCreationHandlerTestprozess;0~1

## Dependencies

Timer: [ERSETZMICH](#)

TIM Version : [ERSETZMICH](#)

From: <https://wiki.tim-solutions.de/> - [TIM Wiki](#) / [NEW TIM 6 Documentation](#)

Permanent link: <https://wiki.tim-solutions.de/doku.php?id=software:tim:timer:createprocessinstancebycsvhandler&rev=1467294946>

Last update: **2021/07/01 09:59**

