

Properties

Properties

*Properties

General

Name *

Aufgabenbenachrichtigungs Mails

Email-Notification preferred

Notify by group-email

Application-Host

Application-Port

Parameter

Target tab for taskmail links

LDAP

Authentication

LDAP host

LDAP port

Factory initial

Authentication type

DN prefix

DN suffix

Mailserver

DefaultEmail

Smtphost

Smtpport

Start TLS

Disposition Notification To

Smtpprovider requires auth.

Smtpprovider

Smtpproviderpassword

Client

Default language

Support Email Address

Theme

Portal headline

OEM Name

Manufacturer

Delegation allowed for

Fix notes storage

Grouptasks not part of "my Tasks" List

Andere

RSS-Link

Max Filesize

The client profil can be accessed in the [Administrator Client](#)

General

Field	Description
Name	The name of the client is entered in this field.

Licensing

Field	Description
License key	Here, a license key, which sets the maximum number of users and processes, can be entered. However, as this is normally done via license data in the TIM Engine, it is often unnecessary and empty.
Max. Users	In this field, the maximum number of users to be compiled in the corresponding client can be determined.
Max. Processes	Here, the maximum number of processes to be deployed can be entered.

Task Notification E-mails

TIM - Task In Motion uses the following parameters to compose the Taskmails, which are sent to the employees. Also, the **`\${baseLink}** is composed from these parameters.

Field	Description
E-mail notification preference	In order to activate the TIM-Taskmails for all users, the Checkbox must be activated.
Application-Host	Here, the host name of the server on which TIM was installed is displayed.
Application-Port	Here, the port of the server on which TIM was installed is entered.
Parameter	This field should only be adapted, if necessary, by a TIM employee.
Target tab of task mail links	Here, the user can state which tab should be opened when a user has clicked on the link in a task mail. This setting applies to all users who were recently compiled.

LDAP

In this area the LDAP interface to TIM can be set up. Further information is available on [this Page](#).

Field	Description
Authentication	Here, an authentication interface is specified. If this field is empty, the TIM-databank is used automatically. In order to establish a LDAP-Authentication , the parameter „ldap“ has to be entered.
LDAP-Host	If an LDAP-interface is used, the host name (the IP-address) of the LDAP-server has to be entered here.

Field	Description
LDAP-Port	If an LDAP-interface is desired, the port of the LDAP-server has to be entered here (Standard is :389).
Factory Initial	The parameter entered here is needed for the initialization of the LDAP-interface and must match the following: (com.sun.jndi.ldap.LdapCtxFactory).
Kind of Authentication	The kind of data encryption during the transmission of the LDAP-interface has to be entered. The field can contain the parameters "simple" or "digest-md5".
DNS Prefix	Here, a DNS Prefix for the network can be specified, if it is used in the network. In most cases this parameter can stay empty.
DNS Suffix	If a DNS-server exists in the network, the DNS Suffix has to be entered here. The parameter entered here is supplied by the network's IT.
Test the LDAP connection (button)	By clicking on this button, the accuracy of the LDAP-connectivity can be checked. Further information is available on this page .

Mail Server

Field	Description
Smtpp return address	The e-mail address that is displayed as the sender on the TIM-notification mails is entered in this input field.
SmtppHost	Here, the IP or host name of the mail server used has to be entered.
SmtppPort	Here, the port that the mail server follows is entered (standard port :25).
Start TLS	Activates the TLS encryption to the mail server, if desired or necessary.
Absence message to	Returned absence messages can be forwarded to a certain mail box (to be entered here).
Smtpp erfordert Auth.	Activates the authentication to the mail server if necessary.
SmtppUser	Here, the user having the right to send e-mails via the mailserver is entered.
SmtppPassword	Specifies the password of the according Smtpp user.
Test e-mail configuration (button)	By clicking on this button, the dispatching of TIM- notification e-mails can be simulated in order to test their functionality. Further information is available from email_testing

Client

Field	Description
Support Emailaddress	Changes the display of the support e-mail-address in the information area of all Clients .
Theme	In this field, the Theme to be used is displayed. This is the name of the custom file.
Producer	not required
Delegation allowed for	Here it is possible to determine for which context roles delegation (transfer of task to third parties) is allowed. If "Person in charge" is selected, users with the right "member" can delegate tasks to their group's co-workers.

Field	Description
Fix notes depot	If here, for example, process instance is chosen, all notes are attached to the process instance and no longer to tasks. If "task" is chosen as the parameter, but a note is attached to the process instance, the note will still be attached to the instance, as TIM does not know to which task of the instance the note should be attached to.
Group tasks not in "My tasks" list	Tasks tab either displays "my tasks and tasks of my group" or "my tasks only".

From:

<https://wiki.tim-solutions.de/> - **TIM Wiki** / [NEW TIM 6 Documentation](#)

Permanent link:

https://wiki.tim-solutions.de/doku.php?id=en:software:tim:client_profile

Last update: **2021/07/01 09:52**

